

Force / load / airgap table • Alimentación / carga / Tabla espacio de aire • Alimentation / charge / entrefer Tableau

FXV200	Airgap < 0,1mm			Airgap 0,1 - 0,3 mm			Airgap 0,3 - 0,5 mm		
Steel thickness (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)
>= 4	70	1500	1250	50	1500	1250	35	1000	1250
>= 6	110	2000	1250	75	1500	1250	60	1250	1250
>= 8	175	2500	1250	120	2000	1250	90	2000	1250
>= 10	200	2500	1250	140	2000	1250	110	2000	1250
Ø 20-50	100	2000	-	70	2000	-	60	1500	-
90° ✓	100	3000	-	80	2500	-	60	2000	-
90° ^	120	3000	-	100	2500	-	60	2000	-

FXV400	Airgap < 0,2mm			Airgap 0,2 - 0,3 mm			Airgap 0,3 - 0,6 mm		
Steel thickness (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)
>= 6	200	2000	1000	120	1500	1000	100	1250	1000
>= 8	300	2500	1250	210	2250	1250	150	2000	1250
>= 10	340	2500	1250	260	2250	1250	180	2000	1250
>= 15	400	2500	1250	320	2250	1250	220	2000	1250
Ø 20-60	200	3500	-	160	2250	-	120	2500	-
90° ✓	200	4000	-	160	3500	-	120	3200	-
90° ^	250	4000	-	190	3500	-	130	3200	-

FXV800	Airgap < 0,2mm			Airgap 0,2 - 0,3 mm			Airgap 0,3 - 0,6 mm		
Steel thickness (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)	Working Load Limit (kg)	Max. L (mm)	Max. W (mm)
>= 4	125	2000	1500	100	2000	1500	90	2000	1500
>= 6	200	2500	1500	160	2250	1500	130	2250	1500
>= 8	400	3000	1500	320	3000	1500	270	2500	1500
>= 15	650	3000	1500	520	3000	1500	420	2500	1500
>= 20	800	3000	1500	650	3000	1500	550	2500	1500
Ø 35-75	300	4000	-	240	3500	-	200	3000	-
90° ✓	300	5000	-	240	4500	-	200	4000	-
90° ^	400	5000	-	320	4500	-	300	4000	-